





PROUDLY PRODUCED IN CANADA

TESTED IN OUR FORESTS BY THE PROS!

For more than 40 years, our experts have designed and tested loaders in our forests under real-world conditions, thereby ensuring optimal performance.

Our loader is perfect for tree pruners, parks, cities and municipalities for collecting various materials.











A - STABLE

Every trailer is designed to accommodate a loader, guaranteeing exceptional balanceand stability during load and transinrt.

D - INWERFUL AND RELIABLE

Our gasoline-inwered, Honda hydraulic unit withstands Canada's harsh winters and allows you to operate the loader independently from your vehicle. And our LED lights last longer than ever!

B- REVOLUTIONARY GRAPPLE

With its exclusive curve, our grapple makes it easy to ftck up logs without crushing them, increasing lift capacity while preserving wood quality.

E - EXCEPTIONAL QUALITY

At Metavic, the galvanization of our trailers ensures durable equipment. Furthermore, we pay attention to every detail: the wiring and connectors are sealed, and each trailer comes with a roll-up tarp.

C - STEADY TRAILER

The butterfly stabilizer legs attached to the loader allow the trailer to stay put during loading or unloading, keeftng you anchored to the ground!

F - SMOOTH OPERATION

Metavic offers unparalleled efficiency in handling loads, and thanks to our hydraulic control, every task is smooth and precise.

SPECIFICATIONS

Loader	1150M13	1150M14	1150M16
Boom lenght	13 ft	14 ft	16 ft
Loader height	66 in	66 in	66 in
Loader width	40 in	40 in	40 in
Loader rotation	270°	270°	270°
Grapple rotation	Continuous	Continuous	Continuous
Lifting capacity (full reach)	900 lb	900 lb	800 lb
Lifting capacity (half reach)	2 200 lb	2 600 lb	2 500 lb
Opening of the grapple	36 in	36 in	36 in
Closing of the grapple	4,50 in	4,50 in	4,50 in
Honda Hydraulic power plant	9 HP	9 HP	9 HP
Loader weight	1 100 lb	1 200 lb	1 275 lb
Trailer	WD612	WD612	WD714
Trailer total lenght	231 in	231 in	251 in
Interior of the box	147 in x 72 in x 26 in	147 in x 72 in x 26 in	168 in x 82 in x 32 in
Tive o /vive o		OT005/05 D40 40 4	
Tires/rims	ST235/85 R16 12 ply	ST235/85 R16 12 ply	215/75H17.5 16 ply
Axles	ST235/85 R16 12 ply 2 x 7 000 lb	2 x 7 000 lb	215/75H17.5 16 ply 2 x 8 000 lb
Axles	2 x 7 000 lb	2 x 7 000 lb	2 x 8 000 lb
Axles Back trailer height	2 x 7 000 lb 54 in	2 x 7 000 lb 54 in	2 x 8 000 lb 66 in
Axles Back trailer height Exterior width - tires	2 x 7 000 lb 54 in 94 in	2 x 7 000 lb 54 in 94 in	2 x 8 000 lb 66 in 101 1/2 in
Axles Back trailer height Exterior width - tires Height with loader	2 x 7 000 lb 54 in 94 in 90 in	2 x 7 000 lb 54 in 94 in 90 in	2 x 8 000 lb 66 in 101 1/2 in 93 in
Axles Back trailer height Exterior width - tires Height with loader Cylinder force	2 x 7 000 lb 54 in 94 in 90 in 7 tons	2 x 7 000 lb 54 in 94 in 90 in 7 tons	2 x 8 000 lb 66 in 101 1/2 in 93 in 12 tons
Axles Back trailer height Exterior width - tires Height with loader Cylinder force Cylinder stroke	2 x 7 000 lb 54 in 94 in 90 in 7 tons 108 in	2 x 7 000 lb 54 in 94 in 90 in 7 tons 108 in	2 x 8 000 lb 66 in 101 1/2 in 93 in 12 tons 120 in
Axles Back trailer height Exterior width - tires Height with loader Cylinder force Cylinder stroke Loading capacity	2 x 7 000 lb 54 in 94 in 90 in 7 tons 108 in 10 600 lb	2 x 7 000 lb 54 in 94 in 90 in 7 tons 108 in 10 600 lb	2 x 8 000 lb 66 in 101 1/2 in 93 in 12 tons 120 in 11 800 lb
Axles Back trailer height Exterior width - tires Height with loader Cylinder force Cylinder stroke Loading capacity Weight on the pole	2 x 7 000 lb 54 in 94 in 90 in 7 tons 108 in 10 600 lb 975 lb	2 x 7 000 lb 54 in 94 in 90 in 7 tons 108 in 10 600 lb 975 lb	2 x 8 000 lb 66 in 101 1/2 in 93 in 12 tons 120 in 11 800 lb 1 200 lb
Axles Back trailer height Exterior width - tires Height with loader Cylinder force Cylinder stroke Loading capacity Weight on the pole Clip	2 x 7 000 lb 54 in 94 in 90 in 7 tons 108 in 10 600 lb 975 lb 2 5/16 in	2 x 7 000 lb 54 in 94 in 90 in 7 tons 108 in 10 600 lb 975 lb 2 5/16 in	2 x 8 000 lb 66 in 101 1/2 in 93 in 12 tons 120 in 11 800 lb 1 200 lb 2 5/16 in

PERSONALIZED YOUR LOADER

AVAILABLE OPTIONS

Explore ways to customize and enhance the performance of your loader with a Metavic dump trailer. Optimize your equipment for unparalleled versatility and efficiency!

Steel cable

HYDRAULIC WINCH

5/16 IN X 100 FT 6 000 LB Synthetic cable

HYDRAULIC WINCH

5/16 IN X 100 FT 6 000 LB GALVANIZED RAMP

ELECTRIC STARTER



METAVIC

Creating Enjoyment in the Forest.

Since 1982

SCAN THE QR CODE TO VISIT OUR WEBSITE:



1439, Rang 1, Saint-Fterre-Baptiste, Québec G0P 1K0 Phone.: 819 365-4376 - Téléc.: 819 365-9994 Email: info@metavic.ca

www.metavic.ca